

## Klüber Summit DSL 32, 46, 68, 100, 125

Fully synthetic air compressor oils for oil change intervals up to 8,000 operating hours



### Benefits for your application

- **Low maintenance and operating costs due to oil change intervals up to 8,000 operating hours in oil-injected screw-type compressors**
- **Easier compressor oil conversion due to neutral behaviour of oils towards seals**
- **Good soil dissolving capacity, clean oil circuit due to the ester content in the oil, reduction of cleaning costs**
- **Low formation of oxidation residues in the oil circuit, reduced operating costs due to extended oil filter and separator life**
- **Klüber Summit DSL 32, 46, and 68 are biodegradable oils and can be used for sensitive applications like sewage plants**

### Description

Klüber Summit DSL oils are air compressor oils based on a synthetic ester oil and additives. They can be mixed with mineral oils, synthetic hydrocarbon oils and polyglycol oils.

### Application

The Klüber Summit DSL 32 ... 68 oils have been especially designed for oil change intervals up to 8,000 operating hours\* in oil-injected screw-type compressors. Klüber Summit DSL 32 and 46 can also be used for the lubrication of centrifugal compressors, whereas Klüber Summit DSL 68 ... 125 is particularly suitable for the lubrication reciprocating piston compressors.

Klüber Summit DSL oils are used for compressors that were previously run with conventional mineral oils. These oils are neutral towards most elastomer seals used in air compressors, therefore leakage is not to be expected.

Klüber Summit DSL 32 oils are mainly used in reciprocating piston compressors which do not achieve the desired maintenance intervals when using mineral oils or which show severe residue formation (carbon buildups) on valves and in the compression chamber. Klüber Summit DSL 32, 46, and 68 are biodegradable and can therefore be used in eco-sensitive applications.

Klüber Summit DSL oils offer good oxidation stability due to the synthetic base oil, thus minimizing oxidation residues in the compressors and extending oil change intervals and the service life of oil filters and separators (screw-type compressors) and valves (reciprocating piston compressors).

### Application notes

When selecting the oil viscosity for air compressors please observe the manufacturers' instructions.

When switching a used compressor to a Klüber Summit DSL oil, drain old oil from whole circuit of compressor while still warm. We also recommend changing all oil filters and separators. Then refill the compressor with Klüber Summit DSL oil.

When switching from mineral oil to a synthetic Klüber Summit DSL oil please consider that the compressor may contain oxidation residues in the form of blackened or contaminated oil. As such residues can affect the service life of the fresh Klüber Summit DSL oil, the compressor should be cleaned using the Klüber Summit Varnasolv conditioner (cf. product information leaflet).

Your contact persons at Klüber Lubrication would be pleased to provide further information.

After switching to a Klüber Summit DSL oil we recommend determining the oil change interval through an oil analysis or the Klüber Summit TAN Kit.

### Material safety data sheets

Material safety data sheets can be requested via our website [www.klueber.com](http://www.klueber.com). You may also obtain them through your contact person at Klüber Lubrication.

# Klüber Summit DSL 32, 46, 68, 100, 125

Fully synthetic air compressor oils for oil change intervals up to 8,000 operating hours

Pack sizes	Klüber Summit DSL 32	Klüber Summit DSL 46	Klüber Summit DSL 68	Klüber Summit DSL 100	Klüber Summit DSL 125
Canister 19 l	+	+	+	+	+
Drum 208 l	+	-	-	+	+


Product data	Klüber Summit DSL 32	Klüber Summit DSL 46	Klüber Summit DSL 68	Klüber Summit DSL 100	Klüber Summit DSL 125
Article number	050000	050064	050001	050002	050003
Colour space	yellow	yellow	yellow	yellow	yellow
Density, DIN 51757, 20 °C	approx. 0.94 g/cm <sup>3</sup>	approx. 0.97 g/cm <sup>3</sup>	approx. 0.96 g/cm <sup>3</sup>	approx. 0.96 g/cm <sup>3</sup>	approx. 0.96 g/cm <sup>3</sup>
Foam test, ASTM-D 892, ISO 6247, sequence I/24 °C	<= 50/0 ml	<= 50/0 ml	<= 50/0 ml	<= 50/0 ml	<= 50/0 ml
Foam test, ASTM-D 892, ISO 6247, sequence II/ 93.5 °C	<= 50/0 ml	<= 50/0 ml	<= 50/0 ml	<= 50/0 ml	<= 50/0 ml
Foam test, ASTM D 892, ISO 6247, sequence III/24°C	<= 50/0 ml	<= 50/0 ml	<= 50/0 ml	<= 50/0 ml	<= 50/0 ml
Demulsifying capacity, DIN 51599, ASTM D 1401, at 54 °C	40/37/3 ml	40/37/3 ml	40/37/3 ml		
Biodegradability according to OECD 301 F, (within 28 days)	>= 60 %	>= 60 %	>= 60 %		
Flash point, DIN EN ISO 2592, Cleveland, open-cup apparatus	>= 220 °C	>= 240 °C	>= 240 °C	>= 250 °C	>= 250 °C
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 32 mm <sup>2</sup> /s	approx. 46 mm <sup>2</sup> /s	approx. 68 mm <sup>2</sup> /s	approx. 100 mm <sup>2</sup> /s	approx. 125 mm <sup>2</sup> /s
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C	approx. 5.8 mm <sup>2</sup> /s	approx. 5.7 mm <sup>2</sup> /s	approx. 8.3 mm <sup>2</sup> /s	approx. 10.7 mm <sup>2</sup> /s	approx. 13.4 mm <sup>2</sup> /s
Viscosity index, DIN ISO 2909	>= 70	>= 50	>= 90	>= 90	>= 90
Copper corrosion, DIN EN ISO 2160, 24 h/100°C	1 - 100 corrosion degree	1 - 100 corrosion degree	1 - 100 corrosion degree	1 - 100 corrosion degree	1 - 100 corrosion degree
Pour point, DIN ISO 3016	<= -42 °C	<= -39 °C	<= -36 °C	<= -30 °C	<= -30 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	60 months	60 months	60 months	60 months





## Klüber Summit DSL 32, 46, 68, 100, 125

Fully synthetic air compressor oils for oil change intervals up to 8,000 operating hours



### Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /  
Geisenhausenerstraße 7 / 81379 München / Germany /  
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.