

ANDEROL 783-2

Synthetic Food Grade Grease NLG-2

www.Oil18.ru : 902313@inbox.ru : tel (3412) 902-313

Product Data Sheet



ANDEROL 783-2 is a synthetic hydrocarbon (PAO) based aluminum complex thickened grease designed for use in food processing machinery. It is non-toxic, high quality general-purpose grease and can satisfy a wide variety of applications, even under high temperatures, high loads and water exposure.

ANDEROL 783-2 is NSF registered as H1 for use in applications where incidental food contact can occur.

ADVANTAGES / BENEFITS

- High temperatures, high loads and water exposure
- Excellent wear protection
- Prevent rusting
- Good mechanical stability

COMPATIBILITY

APPLICATION

Lubrication of roller and friction bearings in food and beverage, cosmetic and pharmaceutical industry. High quality general-purpose food grade grease. Grease lubricating points in can seaming and bottling.

PROPERTIES	TEST METHOD	ANDEROL 783-2
Thickener		Al-complex
Color		White
Type of Base Oil		Synthetic (PAO)
Operating temperature for long-term lubrication		-45 to +160 °C
Short time admissible temperature peak value		+200 °C
Dropping Point		>250 °C
Worked Penetration	ASTM D-2265	265 to 295
Base Oil Viscosity at 40°C	ASTM D-217	350 mm ² /s
Water Resistance	ASTM D-445	0-90
Corrosion Protection	DIN 51.807-01	Corrosion degree 0/0
4 Ball-test welding load	IP 220/85	2600 N
Designation	DIN 51.350	KPFHC 2 P-40
Designation	DIN 51.502	XEEHB2
	ISO 6743	

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

APPROVALS / REGISTRATIONS



ANDEROL BV

Punterweg 21 A
6222 NW MAASTRICHT
The NETHERLANDS

Tel No.: +31 (0)43 352 41 90
Fax No.: +31 (0)43 352 41 99
www.anderol-europe.com

This information is furnished without warranty, representation, inducement, or license of any kind except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL to be accurate. ANDEROL does not assume any legal responsibility for use of reliance upon it. Only Chemists or chemically qualified lab technicians should carry out tests. Before using any chemicals, read its label and Material Safety Data Sheet.