

Klüberbio BM 32-142

Environmentally acceptable multi-purpose grease for rolling and plain bearings

Your benefits at a glance

- Complies with the requirements for Environmentally Acceptable Lubricants as defined in Appendix A of the 2013 Vessel General Permit
- The grease's good low-temperature behaviour enables operation at very low ambient temperatures
- Selected additives ensure longer component life and reduced wear
- Longer maintenance intervals due to good resistance to wear and corrosion as well as load-carrying capacity

Your requirements - our solution

As a manufacturer or operator of marine equipment that is frequently subject to extreme ambient conditions and in contact with sea water you are likely to be interested in obtaining an eco-friendly, high-performance operating lubricant.

Our Klüberbio BM 32-142 is a high-performance grease combining very good eco-friendliness with an excellent load-carrying capacity, good antiwear and anticorrosive effect and good low-temperature behaviour.

These performance characteristics make Klüberbio BM 32-142 the preferred multi-purpose product for a variety of applications and components in environmentally sensitive areas.

Klüberbio BM 32-142 also complies with the requirements for classification as an Environmentally Acceptable Lubricant (EAL) in terms of biodegradability, toxicity and bioaccumulation, as defined by the US Environmental Protection Agency for the "2013 Vessel General Permit".

Application

Klüberbio BM 32-142 was developed for the lubrication of rolling and plain bearings with high surface pressure which can get in direct contact with nature. It combines good eco-compatibility with high corrosion protection and load-carrying capacity, making it an ideal lubricant for maritime applications.

Typical applications include bearings in cranes, fairleads, winches and rudder systems.

If you have any questions regarding your application, our experts will be happy to help you.

Application notes

Klüberbio BM 32-142 can be applied by brush, spatula, grease gun or automatic lubricant dispensers, also at low temperatures.

Please note that Klüberbio BM 32-142 takes on a reddish colour under the effects of UV. This does not affect the performance of the lubricating grease.

This product is also available in our automatic lubricant dispenser Klübermatic. Please consult the application engineering experts from Klüber Lubrication to determine whether Klübermatic might be used under the conditions in your processes.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klüberbio BM 32-142
Bucket 25 kg	+
Drum 180 kg	+
Cartridge PA Klübermatic NOVA 125 ml	+

Klüberbio BM 32-142

Environmentally acceptable multi-purpose grease for rolling and plain bearings

Product data	Klüberbio BM 32-142
Article number	009053
Lower service temperature	-40 °C / -40 °F
Upper service temperature	120 °C / 248 °F
Colour space	beige
Density at 20 °C	approx. 0.94 g/cm ³
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 140 mm ² /s
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C	approx. 22 mm ² /s
NLGI grade, DIN 51818	2
Biodegradability according to OECD 301 F, (within 28 days)	>= 60 %
Corrosion inhibiting properties of lubricating greases, DIN 51802, (SKF-EMCOR), test duration: 1 week, distilled water	<= corrosion degree
Copper corrosion, DIN 51811, (lubricating grease), 24h/100°C	1 - 100 corrosion degree
Low-temperature torque, IP 186, -40 °C, start	<= 1 000 mNm
Low-temperature torque, IP 186, -40 °C, running	<= 100 mNm
Speed factor (n x dm)	approx. 300 000 mm/min
Four-ball EP tester, wear value, DIN 51350 part 5, procedure E, 60s/1000N, wear scar diameter	<= 1.8 mm
Water resistance, DIN 51807 pt. 01, 3 h/90 °C, rating	1 - 90
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.